NSN 5305-01-454-5530

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-454-5530

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.750 inches |
| Fastener Length: |
| Between 2.190 inches and 2.250 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.921 inches and 0.937 inches |
| Head Height: |
| Between 0.616 inches and 0.625 inches |
| Locking Feature: |
| Patch threads or pellet threads or strip threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.625 inches |
| Width Across Flats: |
| 0.500 inches |
| Thready Qty Per Inch (tpi): |
| 11 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 33.0 rockwell c fastener and 42.0 rockwell c fastener |
| Minimum Yield Strength: |
| 120000 pounds per square inch |
| Material: |
| Iron alloy 660 fastener |
| Material Specification: |
| Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener |
| Surface Treatment: |
| Passivate fastener |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response fastener |
| Thread Series Designator: |
| Unrc |
| Specification Data: |

80205-nas1352 professional/industrial association standard

NSN 5305-01-454-5530

Socket Head Cap Screw - Page 2 of 2



| | | ife: | |
|--|--|------|--|
| | | | |
| | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0