NSN 5305-01-454-5549

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-454-5549 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** Between 1.460 inches and 1.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: 0.141 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c fastener and 42.0 rockwell c fastener Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660 fastener **Material Specification:** Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener **Surface Treatment:**

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

NSN 5305-01-454-5549

Socket Head Cap Screw - Page 2 of 2



She	lf I	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0