NSN 5305-01-454-7302

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-454-7302 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.100 inches **Fastener Length:** Between 0.845 inches and 0.875 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch **Product Name:** Non-magnetic screw **Special Features:** Magnetic signature requirement: less than 2 gamma (.02 milli gajss) when tested i.A.W. Ws 20522 Material: Steel comp 310 or steel comp 316 **Material Specification:** Astm f593 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-454-7302

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0