NSN 5305-01-455-2107

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-455-2107

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.454 inches |
| Fastener Length: |
| 1.751 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.692 inches and 0.763 inches |
| Grip Diameter: |
| Between 0.3729 inches and 0.3737 inches |
| Internal Drive Style: |
| Cross recess type iii |
| Thread Diameter: |
| 0.375 inches |
| Grip Length: |
| Between 1.302 inches and 1.322 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Q-p-416 ty2cl2 federal specification 13th treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas7506 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-455-2107

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0