NSN 5305-01-455-8608

Socket Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-455-8608



3a Thread Direction: Right-hand Thread Length: Between 1.750 inches and 2.820 inches Fastener Length: Between 2.992 inches and 3.008 inches Head Style: Flat chamfer Head Diameter: Between 0.921 inches and 0.938 inches Head Height: Between 0.616 inches and 0.625 inches Internal Drive Style: Hexagon Thread Diameter: 0.625 inches With Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Iq-n-281 federal specification single material response Thread Series Designator: Inc Shelf Life: N/a Dint Of Measure: Image: No Shelf Life: Na Shelf Life: Na Shelf Life: Na	Thread Class:
Right-handRight-handThread Length:Between 1.750 inches and 2.820 inchesFastener Length:Between 2.992 inches and 3.008 inchesHead Style:Flat chamferHead Diameter:Between 0.921 inches and 0.938 inchesHead Height:Between 0.921 inches and 0.625 inchesInternal Drive Style:HexagonThread Diameter:0.625 inchesWidth Across Flats:0.500 inchesThready Qty Per Inch (tpi):11Min. Tensile Strength (psi):80000 pounds per square inchMaterialCopper alloyMaterial Specification:Qq-n-281 federal specification single material responseThread Series Designator:UncShelf Life:N/aNiFig:NoFig:	3a
Thread Length: Between 1.750 inches and 2.820 inches Fastener Length: Between 2.992 inches and 3.008 inches Head Style: Flat chamfer Head Diameter: Between 0.921 inches and 0.938 inches Head Height: Between 0.616 inches and 0.625 inches Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material Qq-n-281 federal specification single material response Thread Stries Designator: Unc Shelf Life: N/a Pint Of Measure: - Demilitarization: No Fig:	Thread Direction:
Between 1.750 inches and 2.820 inches Fastener Length: Between 2.992 inches and 3.008 inches Head Style: Flat chamfer Head Diameter: Between 0.921 inches and 0.938 inches Head Height: Between 0.921 inches and 0.625 inches Head Height: Between 0.616 inches and 0.625 inches Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Right-hand
Fastener Length:Between 2.992 inches and 3.008 inchesHead Style:Flat chamferHead Diameter:Between 0.921 inches and 0.938 inchesHead Height:Between 0.616 inches and 0.625 inchesInternal Drive Style:HexagonThread Diameter:0.625 inchesWidth Across Flats:0.500 inchesThready Qty Per Inch (tpi):11Min. Tensile Strength (psi):80000 pounds per square inchMaterial:Copper alloyMaterial Specification:UncShelf Life:N/aUnit Of Measure:TToPinilitarization:NoFig:	Thread Length:
Between 2.992 inches and 3.008 inches Head Style: Flat chamfer Head Diameter: Between 0.921 inches and 0.938 inches Head Height: Between 0.616 inches and 0.625 inches Head Diameter: Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Vidth Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 1.750 inches and 2.820 inches
Head Style: Flat chamfer Head Diameter: Between 0.921 inches and 0.938 inches Head Height: Between 0.616 inches and 0.625 inches Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Fastener Length:
Flat chamferHead Diameter:Between 0.921 inches and 0.938 inchesHead Height:Between 0.616 inches and 0.625 inchesInternal Drive Style:HexagonThread Diameter:0.625 inchesWidth Across Flats:0.500 inchesThready Qty Per Inch (tpi):11Min. Tensile Strength (psi):80000 pounds per square inchMaterial:Copper alloyMaterial Specification:Qq-n-281 federal specification single material responseThread Series Designator:UncShelf Life:N/aUnit Of Measure:-Pemilitarization:NoFig:	Between 2.992 inches and 3.008 inches
Head Diameter:Between 0.921 inches and 0.938 inchesHead Height:Between 0.616 inches and 0.625 inchesInternal Drive Style:HexagonThread Diameter:0.625 inchesWidth Across Flats:0.500 inchesThready Qty Per Inch (tpi):11Min. Tensile Strength (psi):80000 pounds per square inchMaterial:Copper alloyMaterial Specification:Qq-n-281 federal specification single material responseThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Head Style:
Between 0.921 inches and 0.938 inches Head Height: Between 0.616 inches and 0.625 inches Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Flat chamfer
Head Height: Between 0.616 inches and 0.625 inches Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Head Diameter:
Between 0.616 inches and 0.625 inches Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 In Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.921 inches and 0.938 inches
Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Head Height:
Hexagon Thread Diameter: 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.616 inches and 0.625 inches
Thread Diameter:0.625 inchesWidth Across Flats:0.500 inchesThready Qty Per Inch (tpi):11Min. Tensile Strength (psi):80000 pounds per square inchMaterial:Copper alloyMaterial Specification:Qq-n-281 federal specification single material responseThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Internal Drive Style:
0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Hexagon
Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Diameter:
0.500 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.625 inches
Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Width Across Flats:
11 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.500 inches
Min. Tensile Strength (psi): 80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thready Qty Per Inch (tpi):
80000 pounds per square inch Material: Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	11
Material:Copper alloyMaterial Specification:Qq-n-281 federal specification single material responseThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Min. Tensile Strength (psi):
Copper alloy Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	80000 pounds per square inch
Material Specification: Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Qq-n-281 federal specification single material response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Copper alloy
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Specification:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Qq-n-281 federal specification single material response
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unc
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A003b0	Fiig:
	A003b0