## NSN 5305-01-456-0024

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-456-0024

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.155 inches	
Fastener Length:	
Between 0.171 inches a	nd 0.218 inches
Head Style:	
Hexagon	
Head Height:	
Between 0.049 inches a	nd 0.060 inches
Width Between Flats:	
Between 0.181 inches a	nd 0.189 inches
nternal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.112 inches	
Thready Qty Per Inch	tpi):
40	
Min. Tensile Strength	psi):
160000 pounds per squ	are inch
Hardness Rating:	
Between 36.0 rockwell	and 40.0 rockwell c
Screw Material:	
Steel comp e4340 or st	el comp 8740
Screw Material Specifi	cation:
Vil-s-5000 military spec	fication 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response	
Screw Surface Treatm	ent:
Cadmium and chromate	
Screw Surface Treatm	ent Specification:
Qq-p-416, ty2, cl2 fede	ral specification all treatment responses
Thread Series Designation	tor:
Unjc	
Specification Data:	
80205-nas1801 profess	onal/industrial association standard
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

## NSN 5305-01-456-0024

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-5000 spec.

