## NSN 5305-01-456-0193

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-456-0193 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.500 inches and 2.380 inches **Fastener Length:** Between 3.170 inches and 3.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: 0.375 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Material: Titanium alloy **Material Specification:** Mil-s-1222, grt7 military specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ams2468 assn standard single treatment response **Thread Series Designator:** Unrc

Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No

## NSN 5305-01-456-0193

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-1222 spec.