## NSN 5305-01-456-1063



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-456-1063 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.180 inches and 0.190 inches **Fastener Length:** Between 0.745 inches and 0.755 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.099 inches and 0.110 inches **First Diameter From Head:** Between 0.135 inches and 0.145 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.470 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Qq-s-764 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification single material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

--

Unf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-01-456-1063

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0