

View Online at <https://aerobasegroup.com/nsn/5305-01-456-1063>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.180 inches and 0.190 inches

**Fastener Length:**

Between 0.745 inches and 0.755 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.099 inches and 0.110 inches

**First Diameter From Head:**

Between 0.135 inches and 0.145 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.470 inches

**Point Style:**

Cone

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 303 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316

**Material Specification:**

Qq-s-764 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification single material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0