

View Online at <https://aerobasegroup.com/nsn/5305-01-456-1063>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.180 inches and 0.190 inches

Fastener Length:

Between 0.745 inches and 0.755 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.099 inches and 0.110 inches

First Diameter From Head:

Between 0.135 inches and 0.145 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.470 inches

Point Style:

Cone

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 303 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

Qq-s-764 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification single material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0