NSN 5305-01-456-4277

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-456-4277 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.355 inches and 0.395 inches **Fastener Length:** Between 0.735 inches and 0.765 inches **Head Style:** Hexagon **Head Height:** Between 0.159 inches and 0.164 inches Width Between Flats: Between 0.262 inches and 0.270 inches **Internal Drive Style:** Hexagon **End Application:** F16a, f16b common **Thread Diameter:** 0.164 inches Width Across Flats: 0.141 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Product Name:** Screw, captive Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard 1st material response or ams5732 assn standard 2nd material response or ams5737 assn standard 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-456-4277

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0