## NSN 5305-01-456-6318

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-456-6318 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.330 inches **Fastener Length:** 0.880 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.099 inches and 0.110 inches **First Diameter From Head:** 0.150 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.550 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.192 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Qq-s-763 federal specification single material response or qq-s-764 federal specification 1st material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-456-6318

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0