

View Online at <https://aerobasegroup.com/nsn/5305-01-457-3848>

**Thread Direction:**

Right-hand

**Thread Length:**

3.70 millimeters

**Fastener Length:**

Between 4.70 millimeters and 5.30 millimeters

**Head Style:**

Flat fillister

**Head Diameter:**

Between 5.32 millimeters and 5.50 millimeters

**Head Height:**

Between 2.89 millimeters and 3.00 millimeters

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

3.0 millimeters

**Width Across Flats:**

Between 2.52 millimeters and 2.56 millimeters

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Pitch In Millimeters:**

0.5

**External Thread Tolerance Class:**

6g

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304

**Material Specification:**

Ams5688 assn standard 1st material response or ams5640 assn standard 2nd material response or ams5617 assn standard 3rd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0