## NSN 5305-01-457-3848



Socket Head Cap Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-457-3848 **Thread Direction:** Right-hand Thread Length: 3.70 millimeters **Fastener Length:** Between 4.70 millimeters and 5.30 millimeters **Head Style:** Flat fillister **Head Diameter:** Between 5.32 millimeters and 5.50 millimeters **Head Height:** Between 2.89 millimeters and 3.00 millimeters **Internal Drive Style:** Hexagon **Thread Diameter:** 3.0 millimeters Width Across Flats: Between 2.52 millimeters and 2.56 millimeters Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Pitch In Millimeters:** 0.5 **External Thread Tolerance Class:** 6g Material: Steel comp 302 or steel comp 303 or steel comp 304 **Material Specification:** Ams5688 assn standard 1st material response or ams5640 assn standard 2nd material response or ams5617 assn standard 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Μ Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:**