## NSN 5305-01-458-1709

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-458-1709 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 0.798 inches and 0.828 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.577 inches and 0.635 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1155 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-458-1709

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0