NSN 5305-01-458-2532



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-458-2532 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.158 inches and 0.178 inches **Fastener Length:** Between 0.440 inches and 0.460 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.168 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Stainless steel or steel **Screw Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Special Features:** 0.0120 inch diameter undfecut under head **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Fiig:

A500d0

Demilitarization:

NSN 5305-01-458-2532

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.