Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-458-2596

| Thread Class:  |
|--|
| За   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 1.000 inches   |
| Fastener Length:   |
| Between 2.015 inches and 2.055 inches  |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.265 inches and 0.375 inches  |
| Head Height:   |
| Between 0.244 inches and 0.250 inches  |
| Internal Drive Style:  |
| Hexagon  |
| Thread Diameter:   |
| 0.250 inches   |
| Width Across Flats:  |
| Between 0.1875 inches and 0.1900 inches  |
| Thready Qty Per Inch (tpi):  |
| 20   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Hardness Rating:   |
| 33.0 rockwell c and 42.0 rockwell c  |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| Unrc   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
|  |

## NSN 5305-01-458-2596

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

