## NSN 5305-01-458-2953



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-458-2953 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.302 inches and 0.322 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.226 inches **Head Height:** 0.138 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.260 inches and 0.310 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 8000 pounds per square inch **Hardness Rating:** 80.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-458-2953

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0