Hexagon Head Cap Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-458-3779

Thread Direction: Right-hand Thread Length: 15.08 millimeters Fastener Length: Between 19.58 millimeters and 20.42 millimeters Head Style: Hexagon Head Height: Between 6.2 millimeters and 6.5 millimeters Width Between Flats: Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class: 6g
Thread Length: 15.08 millimeters Fastener Length: Between 19.58 millimeters and 20.42 millimeters Head Style: Hexagon Head Height: Between 6.2 millimeters and 6.5 millimeters Width Between Flats: Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
15.08 millimeters Fastener Length: Between 19.58 millimeters and 20.42 millimeters Head Style: Hexagon Head Height: Between 6.2 millimeters and 6.5 millimeters Width Between Flats: Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
Fastener Length:Between 19.58 millimeters and 20.42 millimetersHead Style:HexagonHead Height:Between 6.2 millimeters and 6.5 millimetersWidth Between Flats:Between 15.7 millimeters and 16.0 millimetersThread Diameter:10.0 millimetersThread Pitch In Millimeters:1.5External Thread Tolerance Class:
Between 19.58 millimeters and 20.42 millimeters Head Style: Hexagon Head Height: Between 6.2 millimeters and 6.5 millimeters Width Between Flats: Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
Head Style: Hexagon Head Height: Between 6.2 millimeters and 6.5 millimeters Width Between Flats: Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
Hexagon Head Height: Between 6.2 millimeters and 6.5 millimeters Width Between Flats: Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
Head Height: Between 6.2 millimeters and 6.5 millimeters Width Between Flats: Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
Between 6.2 millimeters and 6.5 millimeters Width Between Flats: Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
Width Between Flats: Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
Between 15.7 millimeters and 16.0 millimeters Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
Thread Diameter: 10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
10.0 millimeters Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
Thread Pitch In Millimeters: 1.5 External Thread Tolerance Class:
1.5 External Thread Tolerance Class:
External Thread Tolerance Class:
60
Material:
Steel property class 8.8
Material Specification:
Iso 898-1 national specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Iso 4042 national specification single treatment response
Thread Series Designator:
Μ
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0