NSN 5305-01-458-4252

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-458-4252 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.984 inches and 1.032 inches **Fastener Length:** 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** 0.469 inches **Head Height:** 0.250 inches **Locking Feature:** Strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.3125 inches Width Across Flats: 0.187 inches Thready Qty Per Inch (tpi): **Hardness Rating:** 81.7 rockwell b Minimum Yield Strength: 6026 pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Mil-t9047 comp 7 military specification single material response **Surface Treatment:** Anodize and lubricant **Surface Treatment Specification:** Ams2488b type 2 assn standard 1st treatment response and mil-l-46010 type 2 military specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-458-4252

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.