

NSN 5305-01-458-7158 Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-458-7158 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.282 inches **Fastener Length:** Between 0.343 inches and 0.375 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style: Primary Washer Outside Diameter:** 0.253 inches

Secondary Washer Outside Diameter:

Between 0.253 inches and 0.263 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

Between 0.031 inches and 0.037 inches

Secondary Washer Material Thickness:

Between 0.013 inches and 0.019 inches

Material:

Copper alloy 260 fastener

Material Specification:

Qq-b-613 comp 11 federal specification single material response secondary washer

NSN 5305-01-458-7158

Assembled Washer Screw - Page 2 of 2



Surface Treatment:
Tin
Thread Series Designator:
Unc
Specification Data:
80205-nas1301 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0