Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-458-7158

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.282 inches
Fastener Length:
Between 0.343 inches and 0.375 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Washer Quantity:
2
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
55000 pounds per square inch
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.253 inches
Secondary Washer Outside Diameter:
Between 0.253 inches and 0.263 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
Between 0.031 inches and 0.037 inches
Secondary Washer Material Thickness:
Between 0.013 inches and 0.019 inches
Material:
Copper alloy 260 fastener
Material Specification:
On h C10 comm 11 foderal encolfication single material resumes a second survey have

Qq-b-613 comp 11 federal specification single material response secondary washer

## NSN 5305-01-458-7158

Assembled Washer Screw - Page 2 of 2



Surface Treatment:

Tin

**Thread Series Designator:** 

Unc

Specification Data:

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0