## NSN 5305-01-458-7162

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-458-7162

View Offiline at https://derobasegroup.com/hish/5505-01-450-7102
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.450 inches
Fastener Length:
Between 1.500 inches and 1.562 inches
Head Style:
Pan
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
Between 0.070 inches and 0.080 inches
Locking Feature:
Strip
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response or ams 5853 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1190 professional/industrial association standard
Shelf Life:
N/a

**Unit Of Measure:** 

## NSN 5305-01-458-7162

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0