NSN 5305-01-458-7585

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-458-7585 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.725 inches and 0.745 inches **Fastener Length:** Between 1.610 inches and 1.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.959 inches and 1.017 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas 4006 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-458-7585

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0