NSN 5305-01-459-0768

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-459-0768 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.148 inches and 0.160 inches **Fastener Length:** Between 0.460 inches and 0.480 inches **Head Style:** Fillister **Head Diameter:** 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.320 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.0937 inches and 0.0952 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type c class 3 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-459-0768

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0