

View Online at <https://aerobasegroup.com/nsn/5305-01-460-2905>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.750 inches

**Fastener Length:**

Between 3.837 inches and 3.927 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Screw Material:**

Steel comp 4140 or steel comp e4340 or steel comp 8740

**Screw Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas600 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5626 spec.