

View Online at <https://aerobasegroup.com/nsn/5305-01-461-2648>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.312 inches

Fastener Length:

0.395 inches

Head Style:

Pan no. 2

Head Diameter:

0.271 inches

Head Height:

0.083 inches

Internal Drive Style:

Slot

End Application:

5895-21-913-2722 interface unit, communication equipment nau3-1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32.0

Product Name:

Seelskrew, high-pressure, self-sealing, pan head s-slotted

Screw Material:

Steel

Bearing Surface Of Head Surface Treatment:

Oxide

Head Surface Treatment:

Oxide

Bearing Surface Of Head Surface Treatment Specification:

Mil-c-13924c military specification single treatment response

Head Surface Treatment Specification:

Mil-c-13924c military specification single treatment response

Special Features:

Part number suffix 2615 indicates flourisilicone o-ring; seals out air, water, gas, various contaminants; vibration resistant; groove underneath head accomodates o-ring

Color:

Black

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924c spec.