

View Online at <https://aerobasegroup.com/nsn/5305-01-461-2648>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.312 inches

**Fastener Length:**

0.395 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

0.271 inches

**Head Height:**

0.083 inches

**Internal Drive Style:**

Slot

**End Application:**

5895-21-913-2722 interface unit, communication equipment nau3-1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32.0

**Product Name:**

Seelskrew, high-pressure, self-sealing, pan head s-slotted

**Screw Material:**

Steel

**Bearing Surface Of Head Surface Treatment:**

Oxide

**Head Surface Treatment:**

Oxide

**Bearing Surface Of Head Surface Treatment Specification:**

Mil-c-13924c military specification single treatment response

**Head Surface Treatment Specification:**

Mil-c-13924c military specification single treatment response

**Special Features:**

Part number suffix 2615 indicates flourisilicone o-ring; seals out air, water, gas, various contaminants; vibration resistant; groove underneath head accomodates o-ring

**Color:**

Black

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-c-13924c spec.