NSN 5305-01-462-1649

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-462-1649

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.794 inches |
| Fastener Length: |
| Between 0.135 inches and 0.168 inches |
| Head Style: |
| Flush |
| Head Diameter: |
| Between 0.690 inches and 0.710 inches |
| Head Height: |
| 0.722 inches |
| Grip Diameter: |
| Between 0.514 inches and 0.515 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| Between 0.428 inches and 0.448 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 30900 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp h11 |
| Material Specification: |
| Ams6487 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Nas672 assn standard single treatment response |
| Thread Series Designator: |
| Unif |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| J JI MOUGUIO. |

--

NSN 5305-01-462-1649

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0