NSN 5305-01-462-2667

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-462-2667 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.641 inches **Fastener Length:** Between 1.438 inches and 1.468 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.752 inches and 0.762 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** High-torque **End Application:** Structural section; f18 aircraft **Thread Diameter:** 0.3750 inches **Grip Length:** 0.812 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Agav

Product Name:

Screw-close tolerance, 100 degree countersunk, dovetail slot, sealant injection

Special Features:

Tapped hole in the head 0.1380-32 unjc-3b threads; distance from top of head to injection port 0.510 in.; injection port 0.120 long, 0.060 wide

Material:

Steel comp xm-13

Material Specification:

Ams5629, ph13-8mo assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 assn standard single treatment response

Thread Series Designator:

Unjf

NSN 5305-01-462-2667

Close Tolerance Screw - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0