NSN 5305-01-462-2725

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-462-2725 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Fastener Length:** Between 0.893 inches and 0.923 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.373 inches and 0.381 inches **Head Height:** 0.084 inches **Spline Minor Diameter:** Between 0.111 inches and 0.113 inches **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Grip Diameter:** Between 0.189 inches and 0.190 inches **Internal Drive Style:** Torx **End Application:** Used on fa-18 e&f **Thread Diameter:** 0.190 inches **Grip Length:** 0.563 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree tension head, gear drive recess Material: Titanium alloy **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5305-01-462-2725

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0