NSN 5305-01-462-2726

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-462-2726

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.425 inches |
| Fastener Length: |
| Between 1.160 inches and 1.190 inches |
| Head Style: |
| Flat countersunk undercut |
| Head Diameter: |
| Between 0.497 inches and 0.507 inches |
| Head Height: |
| 0.110 inches |
| Spline Minor Diameter: |
| Between 0.157 inches and 0.160 inches |
| Spline Major Diameter: |
| Between 0.220 inches and 0.223 inches |
| Grip Diameter: |
| Between 0.249 inches and 0.250 inches |
| Internal Drive Style: |
| Torx |
| End Application: |
| Used on fa-18 e&f |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 0.563 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Product Name: |
| Bolt, 100 degree tension head, gear drive recess |
| Material: |
| Titanium alloy |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |

NSN 5305-01-462-2726

Close Tolerance Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0