

View Online at <https://aerobasegroup.com/nsn/5305-01-462-2742>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.692 inches

Fastener Length:

Between 2.1135 inches and 2.1605 inches

Head Style:

Flat countersunk undercut

Head Diameter:

0.692 inches

Head Height:

Between 0.1147 inches and 0.1167 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Internal Drive Style:

High-torque

End Application:

Structural compenents; f18 aircraft

Thread Diameter:

0.3750 inches

Grip Length:

Between 1.4275 inches and 1.4475 inches

Features Provided:

O ring and cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Criticality Code Justification:

Agav

Product Name:

Screw, close tolerance-assembly, 100 degree countersunk sealing head, dovetail slot, cres

Special Features:

O-ring material - flourosilicone rubber per mil-r-25988, type i, class 1, grade 70

Material:

Steel comp xm-13

Material Specification:

Ams5629, ph13-8mo assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0