NSN 5305-01-462-2743

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-462-2743

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.363 inches |
| Fastener Length: |
| Between 0.598 inches and 0.628 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.360 inches and 0.374 inches |
| Head Height: |
| Between 0.115 inches and 0.125 inches |
| Spline Major Diameter: |
| Between 0.1540 inches and 0.1560 inches |
| Internal Drive Style: |
| Torx |
| End Application: |
| F18e/f |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 3180 pounds per square inch |
| Criticality Code Justification: |
| Agav |
| Product Name: |
| (inavy)screw, machine; boeing bolt-pan head, geardrive |
| Screw Material: |
| Titanium alloy |
| Screw Material Specification: |
| Aia/nas 4004 assn standard single material response |
| Special Features: |
| Drilled 0.075" diameter hole on bolt end |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5305-01-462-2743

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0