## NSN 5305-01-462-2832

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-462-2832 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.035 inches and 1.065 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.497 inches and 0.507 inches **Head Height:** 0.110 inches **Spline Minor Diameter:** Between 0.157 inches and 0.160 inches **Spline Major Diameter:** Between 0.220 inches and 0.223 inches **Grip Diameter:** Between 0.249 inches and 0.250 inches **Internal Drive Style:** Torx **End Application:** Used on fa-18 e&f **Thread Diameter:** 0.250 inches **Grip Length:** 0.625 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree tension head, gear drive recess Material: Titanium alloy **Thread Series Designator:** Unjf

Shelf Life: N/a

## NSN 5305-01-462-2832

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0