

View Online at <https://aerobasegroup.com/nsn/5305-01-462-3462>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

0.500 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.340 inches and 0.385 inches

Internal Drive Style:

Cross recess type ii

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 100.0 degrees

Criticality Code Justification:

Zzzy

Screw Material:

Stainless steel

Locking Feature Material Specification:

Mil-f-18240 military specification single material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Special Features:

Item must comply with requirements of defense supply center philadelphia production standard po0302nrp

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Specification Or Standard:

3 type and 3c style

Departure From Cited Document:

As modified by material and locking feature

Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hs quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-18240 spec.