Hexagon Head Cap Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-463-3051

| Thr | read Direction: |
|------|---|
| Rig | ht-hand |
| Thr | read Length: |
| 8.6 | 5 millimeters |
| Fas | stener Length: |
| Bet | ween 11.65 millimeters and 12.35 millimeters |
| Неа | ad Style: |
| He> | kagon |
| Hea | ad Height: |
| Bet | ween 3.85 millimeters and 4.15 millimeters |
| Wio | dth Between Flats: |
| Bet | ween 9.78 millimeters and 10.00 millimeters |
| Thr | read Diameter: |
| 6.0 | millimeters |
| Thr | read Pitch In Millimeters: |
| 1.0 | |
| Ext | ernal Thread Tolerance Class: |
| 6g | |
| Mat | terial: |
| Ste | el property class 8.8 |
| Mat | terial Specification: |
| lso | 898-1 national specification single material response |
| Sur | rface Treatment: |
| Zin | c |
| Sur | rface Treatment Specification: |
| lso | 4042 national specification single treatment response |
| Thr | read Series Designator: |
| М | |
| She | elf Life: |
| N/a | |
| Uni | it Of Measure: |
| | |
| | militarization: |
| No | |
| Fiig | j: |
| A00 | 03b0 |
| | |
| | |
| | |