Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-463-4317

| Thread Direction: | |
|---|--|
| Right-hand | |
| Thread Length: | |
| 14.83 millimeters | |
| Fastener Length: | |
| Between 19.58 millimeters and 20.42 millimeters | |
| Head Style: | |
| Flat chamfer | |
| Head Diameter: | |
| Between 12.73 millimeters and 13.27 millimeters | |
| Head Height: | |
| Between 7.64 millimeters and 8.00 millimeters | |
| Internal Drive Style: | |
| Hexagon | |
| Thread Diameter: | |
| 8.0 millimeters | |
| Width Across Flats: | |
| 6.0 millimeters | |
| Min. Tensile Strength (psi): | |
| 113784 pounds per square inch | |
| Thread Pitch In Millimeters: | |
| 1.25 | |
| External Thread Tolerance Class: | |
| 6g | |
| Material: | |
| Steel property class 8.8 | |
| Material Specification: | |
| Iso 898-1 national specification single material response | |
| Surface Treatment: | |
| Zinc and chromate | |
| Surface Treatment Specification: | |
| Iso 4042 national specification single treatment response | |
| Thread Series Designator: | |
| Μ | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |
| | |