NSN 5305-01-463-9551

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-463-9551

Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
0.277 inches						
Fastener Length:						
Between 0.387 inches and 0.417 inches						
Head Style:						
Pan						
Head Diameter:						
Between 0.256 inches and 0.270 inches						
Head Height:						
Between 0.087 inches and 0.097 inches						
Internal Drive Style:						
Torque-set ribbed						
Thread Diameter:						
0.138 inches						
Thready Qty Per Inch (tpi):						
32						
Min. Tensile Strength (psi):						
160000 pounds per square inch						
Hardness Rating:						
Between 36.0 rockwell c and 40.0 rockwell c						
Screw Material:						
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150						
Screw Surface Treatment:						
Cadmium and chromate						
Screw Surface Treatment Specification:						
Qq-p-416 type 2 cl 2 federal specification single treatment response						
Bearing Surface Of Head Surface Finish:						
32.0 microinches						
Shank Surface Finish:						
32.0 microinches						
Thread Surface Finish:						
32.0 microinches						
Thread Series Designator:						
Unjc						
Specification Data:						
80205-nas1218 professional/industrial association standard						
Shelf Life:						

N/a

NSN 5305-01-463-9551

Machine Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A500d0