NSN 5305-01-464-0615

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-464-0615

3a Thread Direction: Right-hand Thread Length: 0.276 inches Fastener Length: Between 3.011 inches and 3.041 inches Head Style: Flat countersunk Head Diameter: Between 0.221 inches and 0.279 inches Grip Diameter: Between 0.1365 inches and 0.1375 inches Internal Drive Style:
Right-hand Thread Length: 0.276 inches Fastener Length: Between 3.011 inches and 3.041 inches Head Style: Flat countersunk Head Diameter: Between 0.221 inches and 0.279 inches Grip Diameter: Between 0.1365 inches and 0.1375 inches
Thread Length: 0.276 inches Fastener Length: Between 3.011 inches and 3.041 inches Head Style: Flat countersunk Head Diameter: Between 0.221 inches and 0.279 inches Grip Diameter: Between 0.1365 inches and 0.1375 inches
0.276 inches Fastener Length: Between 3.011 inches and 3.041 inches Head Style: Flat countersunk Head Diameter: Between 0.221 inches and 0.279 inches Grip Diameter: Between 0.1365 inches and 0.1375 inches
Fastener Length:Between 3.011 inches and 3.041 inchesHead Style:Flat countersunkHead Diameter:Between 0.221 inches and 0.279 inchesGrip Diameter:Between 0.1365 inches and 0.1375 inches
Between 3.011 inches and 3.041 inches Head Style: Flat countersunk Head Diameter: Between 0.221 inches and 0.279 inches Grip Diameter: Between 0.1365 inches and 0.1375 inches
Head Style: Flat countersunk Head Diameter: Between 0.221 inches and 0.279 inches Grip Diameter: Between 0.1365 inches and 0.1375 inches
Flat countersunk Head Diameter: Between 0.221 inches and 0.279 inches Grip Diameter: Between 0.1365 inches and 0.1375 inches
Head Diameter:Between 0.221 inches and 0.279 inchesGrip Diameter:Between 0.1365 inches and 0.1375 inches
Between 0.221 inches and 0.279 inches Grip Diameter: Between 0.1365 inches and 0.1375 inches
Grip Diameter: Between 0.1365 inches and 0.1375 inches
Between 0.1365 inches and 0.1375 inches
Internal Drive Style
Offset cruciform (torque set)
Thread Diameter:
0.138 inches
Grip Length:
2.750 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1151 professional/industrial association standard

NSN 5305-01-464-0615

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

