

View Online at <https://aerobasegroup.com/nsn/5305-01-464-0615>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.276 inches

**Fastener Length:**

Between 3.011 inches and 3.041 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.221 inches and 0.279 inches

**Grip Diameter:**

Between 0.1365 inches and 0.1375 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.138 inches

**Grip Length:**

2.750 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1151 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0