## NSN 5305-01-464-8399

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-464-8399 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** Between 1.335 inches and 1.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Hole Diameter:** Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Round internal hexagon Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 

Unrf

**Thread Series Designator:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-464-8399

Socket Head Cap Screw - Page 2 of 2



~n	$\Delta C$ IT	100	HINE	<b>1</b> 1 1	212
JU	CUII	166	ıtior	·	ala.

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A003b0