NSN 5305-01-464-9562

Machine Screw - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5305-01-464-9562

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.359 inches and 0.391 inches
Fastener Length:
Between 0.407 inches and 0.469 inches
Head Style:
Round extended washer
Head Diameter:
0.375 inches
Head Height:
Between 0.025 inches and 0.030 inches
Extended Washer Diameter:
0.437 inches
Extended Washer Thickness:
Between 0.028 inches and 0.033 inches
Internal Drive Style:
Cross recess type ii
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Steel comp 4340
Screw Material Specification:
Ams 6415 assn standard single material response or mil-s-6049 military specification single material response
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Qq-p-416 ty ii cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5305-01-464-9562

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6049 spec.