## NSN 5305-01-465-3213

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-465-3213 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.4063 inches and 0.4687 inches **Fastener Length:** 0.938 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.4688 inches and 0.5312 inches **Head Height:** Between 0.1875 inches and 0.2499 inches **Shoulder Diameter:** 0.3110 inches first shoulder and 0.3120 inches first shoulder **Shoulder Length:** 0.622 inches first shoulder and 0.628 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.1170 inches Thready Qty Per Inch (tpi): 20 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5305-01-465-3213

Shoulder Screw - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A003b0