## NSN 5305-01-465-7815

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-465-7815

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.430 inches and 0.470 inches
Fastener Length:
0.610 inches
Head Style:
Undercut pan no. 2  Head Diameter:
0.482 inches
3.13 <u>-</u> 1.13.133
Head Height:
Between 0.200 inches and 0.240 inches
Internal Drive Style:
Hexagon
End Application:
Ah-64
Material Accommodated Thickness:
0.108 inches
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Product Name:
Screw, captive, self-retracting, crimp-ring style
Lead Thread Quantity:
Two
Special Features:
Grip length 0.120 inch
Material:
Stainless steel stand-off
Material Specification:
Astm a313 assn standard single material response spring
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-465-7815

Panel Screw Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0