
# NSN 5305-01-465-9539

Machine Screw - Page 1 of 2





### **Thread Direction:**

**Right-hand** 

## **Thread Length:**

10.0 millimeters

## Fastener Length:

Between 9.5 millimeters and 10.0 millimeters

## Head Style:

Pan

## Head Diameter:

Between 5.50 millimeters and 5.80 millimeters

#### Head Height:

Between 2.05 millimeters and 2.30 millimeters

#### Locking Feature:

Patch

## Internal Drive Style:

Cross recess type ii

## Thread Diameter:

3.0 millimeters

## **Thread Pitch In Millimeters:**

0.50

# **External Thread Tolerance Class:**

6g

## Screw Material:

Stainless steel

## Locking Feature Material:

Plastic polyamide

## **Screw Material Specification:**

Qq-s-763 federal specification single material response or 66 federal standard single material response

## Locking Feature Material Specification:

L-p-410 federal specification single material response

## Screw Surface Treatment:

Oxide

## Screw Surface Treatment Specification:

Mil-c-13924.Cl4 military specification single treatment response

## **Thread Series Designator:**

Μ

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5305-01-465-9539

Machine Screw - Page 2 of 2

**Fiig:** A500d0

Mil-std (military Standard):

Mil-c-13924 spec.

