NSN 5305-01-466-2539

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-466-2539 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style:** Fillister **Head Diameter:** Between 0.124 inches and 0.140 inches **Head Height:** Between 0.066 inches and 0.083 inches **First Diameter From Head:** Between 0.056 inches and 0.066 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.345 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-466-2539

Externally Relieved Body Screw - Page 2 of 2



			on:	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.