## NSN 5305-01-466-3801

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-466-3801 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 0.746 inches and 0.776 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.226 inches and 0.257 inches **Grip Diameter:** Between 0.1630 inches and 0.1635 inches **Internal Drive Style:** Cross recess type 1 **End Application:** C-17a acft **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degrees reduced head, phillips recess, close tolerance Material: Titanium alloy uns r56440 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas8802 professional/industrial association standard Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-466-3801

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0