Thread Class:

2a

1

20

Hexagon Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-466-7402



Thread Direction: Right-hand Thread Length: Between 0.750 inches and 0.938 inches Fastener Length: Between 1.063 inches and 1.125 inches **Head Style:** Hexagon **Head Height:** Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.4280 inches and 0.4375 inches Hole Diameter: Between 0.0605 inches and 0.0685 inches **Thread Diameter:** 0.250 inches **Hole Quantity:** Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Minimum Yield Strength: 120000 pounds per square inch Hole Configuration Style: Hexagon flats **Special Features:** Drilled head hole diameter: 0.0605 in. Min. And 0.0685 in. Max. Diameter Material: Steel

Material Specification:

Sae j429 grade 8 assn standard single material response or astm a354 grade bd assn standard single material response

Surface Treatment:

Zinc fastener and chromate fastener

Hexagon Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0