NSN 5305-01-466-9126

Close Tolerance Screw - Page 1 of 1

A003b0



View Online at https://aerobasegroup.com/nsn/5305-01-466-9126

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.501 inches |
| Fastener Length: |
| 0.501 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.428 inches and 0.478 inches |
| Grip Diameter: |
| Between 0.311 inches and 0.312 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.311 inches |
| Grip Length: |
| Between 2.615 inches and 2.635 inches |
| Thready Qty Per Inch (tpi): |
| 25 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Material: |
| Stainless steel |
| Material Specification: |
| Ams5731 assn standard 1st material response or ams5732 assn standard 2nd material response or ams5737 assn standard 3rd materia |
| response or ams5853 assn standard 5th material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification 1st treatment response or qq-p-416, ty2, cl2 federal specification 2nd treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |